

- EF compliant to IEC 61280-4-1
- Improves measurement repeatability in multimode fiber test
- Optimised for 850 nm and 1300 nm
- Works with all multimode fiber optic testers



Plug & play Encircled Flux Compliance

The Arden Photonics ModCon Mode Controller is a compact and lightweight module that will modify your LED or VCSEL light source to provide repeatable EF compliant launch conditions.

By simply plugging the ModCon into your light source you will be provided with a stable and consistent EF compliant output that meets IEC 61280-4-1:2009.

How does it work?

Measurements of loss and bandwidth in multimode fibers are highly dependent on the modal condition of the light source used for the measurement. For example, OTDR and LS/PM loss measurements can differ significantly simply because an OTDR uses a laser source and not an LED.


These widely different modal characteristics between sources used in measuring fiber optic systems and networks result in a large and source dependent uncertainty in the accuracy of measurements.

When using a ModCon, you launch the same distribution of modes into the fiber regardless of the source being used and consequently reduce the uncertainty in your measurements due to variation between sources.

In summary the ModCon increases the accuracy of measurements, gives better agreement between test data sets and is a simple and certifiable method of complying with international standards.

Standards compliance and certification

Every ModCon is rigorously tested using Arden's MPX Modal Explorer to ensure that its output meets the standard regardless of the modal distribution of the input. Additionally we can provide a Certificate of Conformance or Test Sheet to aid in fulfilling any of your test equipment record keeping obligations.



(Left)
Plot of typical source showing compliance with the EF requirements in IEC 61280-4-1

Technical Specifications


Physical

Weight	50 g
Dimensions (Excluding Cabling)	153 mm x 36 mm x 10.5 mm
Input Cable Length	1.0 m
Output Cable Length	1.0 m
Input/Output Cable Jacket	3 mm PVC jacket with Aramid strength member
Enclosure material	High strength polymer

Optical

Maximum power throughout	10 mW
Insertion loss @850 nm	50 μ m < 3 dB; 62.5 μ m < 3 dB
Encircled Flux compliance to	IEC 61280-4-1: 2009
Connectors	Reference grade
Component type	Passive
Min. bend radius for ModCon output and EF preserving cord	50 mm

Dimensions (mm)




ModCon EF preserving extender cords

ModCon Encircled Flux preserving extender cords can make the ModCon an even more cost effective and convenient way to ensure EF compliance in your multimode testing. By adding an extender cord to the output connector of your ModCon you can:

- Protect the ModCon output connector from wear, thereby increasing the number of tests you can perform before you need to re-work the connector
- Change connector type on the ModCon output. That means you can test systems with different input connectors just by switching the extender cord. For example you could test systems terminated with both SC and LC connectors with same ModCon just by switching the extender cord.

EF preserving patchcords are specially made and tested to match ModCons. They cannot convert a fiber optic light source which is not EF compliant into a source which is compliant, and cannot be replaced by a standard patchcord.



Ordering Information

Modcon	Description
MC-FC-50-N	Mode controller in 50/125 μ m fiber with FC connectors. Compact, blue body
MC-FC-62-N	Mode controller in 62.5/125 μ m fiber with FC connectors. Compact, blue body
MC-SC-50-N	Mode controller in 50/125 μ m fiber with SC connectors. Compact, blue body
MC-SC-62-N	Mode controller in 62.5/125 μ m fiber with SC connectors. Compact, blue body
MC-SC/LC-50-N	Mode controller in 50/125 μ m fiber with SC/LC connectors. Compact, blue body
MC-SC/LC-62-N	Mode controller in 62.5/125 μ m fiber with SC/LC connectors. Compact, blue body
MC-TE-CC	Certificate of conformance
MC-TE-TC	Test certificate
MC-URT	Return ModCon, re-terminate and re-test input and output connectors

EF Extender Cord	Description
AEP-50-SC/SC-2-S	ModCon EF extender cord, 50/125 μ m fiber, 3mm jacket, 2m long, SC/SC connectors
AEP-50-SC/FC-2-S	ModCon EF extender cord, 50/125 μ m fiber, 3mm jacket, 2m long, SC/FC connectors
AEP-50-SC/LC-2-S	ModCon EF extender cord, 50/125 μ m fiber, 3mm jacket, 2m long, SC/LC connectors
AEP-62-SC/SC-2-S	ModCon EF extender cord, 62.5/125 μ m fiber, 3mm jacket, 2m long, SC/SC connectors
AEP-62-SC/FC-2-S	ModCon EF extender cord, 62.5/125 μ m fiber, 3mm jacket, 2m long, SC/FC connectors
AEP-62-SC/LC-2-S	ModCon EF extender cord, 62.5/125 μ m fiber, 3mm jacket, 2m long, SC/LC connectors

Other connector configurations are available by special order.