



NOTES:
 1) RECOMMENDED PANEL HOLE SEE "DETAIL A"
 2) RECOMMENDED PANEL THICKNESS
 1.2mm TO 2.6mm

DIMENSIONS ARE IN MILLIMETERS.

DRAWN BY: S. BOUJLOV	DATE: 2/04/14	UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW.		 OZ Optics 219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0 www.ozoptics.com	PART BARCODE #: 9
CHECKED BY:	DATE:	INCHES BASIC DIMENSION .XX .XXX BELOW 4 ±.01 ±.005 OVER 4 ±.02 ±.01 MILLIMETERS BASIC DIMENSION .X .XX BELOW 101.6 ±.25 ±.10 OVER 101.6 ±.50 ±.20			DESC. FC Adaptor without Flange
M/S CHECKED BY:	DATE:	ANGULAR DIMENSIONS BASIC DIMENSION X X.X ALL ANGLES ±2.5° ±0.5°		PART NO. SMPC-03-SP	REV N/A
APVD BY:	DATE:	SURFACE FINISH MILLED 125u PROFILED 63u		SIZE: B	DWG.# 3000-0250
PROJECTION:		CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.		SHEET 1 OF 1	SCALE: 5:1